

```

DATASET ACTIVATE DataSet6.
DATASET CLOSE DataSet9.
NEW FILE.
DATASET NAME DataSet10 WINDOW=FRONT.
NPAR TESTS
  /WILCOXON=MCUI WITH MCUII (PAIRED)
  /MISSING ANALYSIS.

```

NPar Tests

Notes

Output Created	01-MAR-2018 16:16:05	
Comments		
Input	Active Dataset	DataSet10
	Filter	<none>
	Weight	<none>
	Split File	<none>
	N of Rows in Working Data File	75
Missing Value Handling	Definition of Missing	User-defined missing values are treated as missing.
	Cases Used	Statistics for each test are based on all cases with valid data for the variable(s) used in that test.
Syntax	NPAR TESTS /WILCOXON=MCUI WITH MCUII (PAIRED) /MISSING ANALYSIS.	
Resources	Processor Time	00:00:00,00
	Elapsed Time	00:00:00,00
	Number of Cases Allowed ^a	112347

a. Based on availability of workspace memory.

[DataSet10]

Wilcoxon Signed Ranks Test

		Ranks	
		N	Mean Rank
sesudahF1000 -	Negative Ranks	18 ^a	25.78

sebelumF1000	Positive Ranks	40 ^b	31.18
	Ties	17 ^c	
	Total	75	

a. sesudahF1000 < sebelumF1000

b. sesudahF1000 > sebelumF1000

c. sesudahF1000 = sebelumF1000

Test Statistics^a

	sesudahF1000 - sebelumF1000
Z	-3,109 ^b
Asymp. Sig. (2-tailed)	.002

a. Wilcoxon Signed Ranks Test

b. Based on negative ranks.



Universitas
Esa Unggul

Universitas
Esa Unggul

Universitas
Esa Unggul

Universitas
Esa U

Universitas
Esa U

Universitas
Esa U

Sum of Ranks
464.00

1247.00

ggul

Universitas
Esa Unggul

Universitas
Esa U

ggul

Universitas
Esa Unggul

Universitas
Esa U

ggul

Universitas
Esa Unggul

Universitas
Esa U