

```

DATASET ACTIVATE DataSet6.
DATASET CLOSE DataSet11.
NEW FILE.
DATASET NAME DataSet14 WINDOW=FRONT.
NPAR TESTS
  /WILCOXON=MCUI WITH MCUII (PAIRED)
  /MISSING ANALYSIS.

```

NPar Tests

Notes

Output Created	01-MAR-2018 16:27:06	
Comments		
Input	Active Dataset	DataSet14
	Filter	<none>
	Weight	<none>
	Split File	<none>
	N of Rows in Working Data File	75
Missing Value Handling	Definition of Missing	User-defined missing values are treated as missing.
	Cases Used	Statistics for each test are based on all cases with valid data for the variable(s) used in that test.
Syntax	NPAR TESTS /WILCOXON=MCUI WITH MCUII (PAIRED) /MISSING ANALYSIS.	
Resources	Processor Time	00:00:00,00
	Elapsed Time	00:00:00,01
	Number of Cases Allowed ^a	112347

a. Based on availability of workspace memory.

[DataSet14]

Wilcoxon Signed Ranks Test

Ranks

		N	Mean Rank
sesudahF6000 -	Negative Ranks	33 ^a	30.95


sebelumF6000	Positive Ranks	29 ^b	32.12
	Ties	13 ^c	
	Total	75	

- a. sesudahF6000 < sebelumF6000
- b. sesudahF6000 > sebelumF6000
- c. sesudahF6000 = sebelumF6000

Test Statistics^a

	sesudahF6000 - sebelumF6000
Z	-.322 ^b
Asymp. Sig. (2-tailed)	.748

- a. Wilcoxon Signed Ranks Test
- b. Based on positive ranks.



Sum of Ranks 1021.50

931.50

ggul

Universitas
Esa Unggul

Universitas
Esa U

ggul

Universitas
Esa Unggul

Universitas
Esa U

ggul

Universitas
Esa Unggul

Universitas
Esa U